

## **Kodak** Point-of-Care **CR 260** System

# Affordable, feature-rich performance

The KODAK Point-of-Care CR 260 System is an affordable computed radiography solution for medium-size healthcare facilities and clinics. Designed to enhance workflow and help improve productivity, the CR 260 System can complement centralized CR and DR environments, serve as a backup or overflow system, and perform in decentralized capture environments such as clinics, ER, and OR departments. All imaging functions can be performed at the point of patient care with this compact package that includes a single-plate CR reader, KODAK flexible phosphor screens, and a PC-based review station.

KODAK Quality Control Workstation Software with its modular design eliminates steps in scanning, processing, and reviewing images for quality assurance. Users can choose resolution scan modes to suit their applications. A USB 2.0 interface enables connection to a variety of devices such as a touch-screen monitor.

### **Highly versatile**

This durable, lightweight, tabletop system expands on the powerful functionality of the KODAK Point-of-Care CR 120 System and KODAK Point-of-Care CR 140 System. It provides throughput of up to 60 plates per hour, with optional high-resolution scanning modes for even greater flexibility.

### **Connectivity and productivity**

KODAK Quality Control Workstation Software, which drives the KODAK Point-of-Care CR 260 System, is designed to streamline clinical workflow and maximize productivity. With its DICOM 3.0 capabilities, the system can be seamlessly integrated with a broad variety of modality equipment, RIS and PACS systems. Mounted on a wheeled Z-cart (optional), it can be conveniently rolled into any situation where instant digital images are needed.

### **Scalability for tomorrow**

The KODAK Point-of-Care CR 260 System is part of the Kodak gallery of healthcare products designed to satisfy your imaging needs. You can start with a small, low-cost digital capture and viewing system that sends images to a diagnostic hard-copy printer or a device that prints images on self-playing CDs. As your practice grows and workloads increase, network multiple KODAK Point-of-Care Systems together to create a distributed CR (D-CR) solution. You can also connect your CR units to a HIS/RIS and PACS, and transmit images wirelessly for teleradiology applications.



## Specifications

### Throughput

- ▶ Up to 60 cassettes per hour

### Time to First Image

- ▶ 37 seconds

### Grayscale Resolution

- ▶ Acquisition: 16 bits per pixel
- ▶ Display: 12 bits per pixel

### Dimensions (H x W x D)

- ▶ 13.4 x 29.0 x 25.8 in. (34.0 x 73.5 x 65.5 cm)

### Weight

- ▶ 99 lbs (45 kg)

### System Configurations

- ▶ Desktop
- ▶ Z-cart (mobile cart)
- ▶ Distributed CR

### Software

- ▶ Integrated acquisition and PACS functionality including: image analysis, archiving, and seamless remote image communications, built on scalable, user-friendly DICOM 3.0 software platform
- ▶ Bone mineral densitometry (BMD OsteoGram<sup>®</sup> software and cassette with template)

### Computer Workstation Minimum Requirements

- ▶ PENTIUM 4 2.4 GHz or higher, 1 GB memory, USB 2.0 ports, CD-RW, 80 GB or larger HD, WINDOWS 2000<sup>®</sup> or WINDOWS XP Professional<sup>®</sup> operating system (small form factor chassis required for Z-cart)

### Power Requirements

- ▶ Single-phase 50/60 Hz, 200 VA, 100-240 VAC (+/- 10%), 2.5A, UPS required

### Regulatory Approvals

- ▶ FDA (USA), CE (EU), SDA (China) and others available or pending in most major markets

### Safety Standards

- ▶ EN 60601-1, 60825-1, 60601-1-2

### Environmental Operating Conditions

- ▶ Operating conditions: 10-40°C, 90% at 35°C  
Storage: -15-60°C

### Cassette Size

#### High Resolution

| Size:                      | Pixel Matrix: | Sampling Density: |
|----------------------------|---------------|-------------------|
| ▶ 8 x 10 in. (20 x 25 cm)  | ▶ 2404 x 2992 | ▶ 8.4 pix/mm      |
| ▶ 10 x 12 in. (25 x 30 cm) | ▶ 2992 x 3584 | ▶ 8.4 pix/mm      |
| ▶ 14 x 14 in. (35 x 35 cm) | ▶ 4172 x 4172 | ▶ 8.4 pix/mm      |
| ▶ 14 x 17 in. (35 x 43 cm) | ▶ 4172 x 5056 | ▶ 8.4 pix/mm      |

#### Standard Resolution

| Size:                      | Pixel Matrix: | Sampling Density: |
|----------------------------|---------------|-------------------|
| ▶ 8 x 10 in. (20 x 25 cm)  | ▶ N/A         | ▶ N/A             |
| ▶ 10 x 12 in. (25 x 30 cm) | ▶ N/A         | ▶ N/A             |
| ▶ 14 x 14 in. (35 x 35 cm) | ▶ 2248 x 2248 | ▶ 5.6 pix/mm      |
| ▶ 14 x 17 in. (35 x 43 cm) | ▶ 2248 x 2724 | ▶ 5.6 pix/mm      |



Health Group  
EASTMAN KODAK COMPANY  
343 State Street  
Rochester, NY 14650

KODAK CANADA INC.  
3500 Eglinton Avenue West  
Toronto, Ontario M6M 1V3  
CANADA

Outside the U.S. or Canada, please  
contact your local Kodak company.

## Kodak

### More information

Learn more about the KODAK Point-of-Care CR 260 System and Kodak's other products for enhanced CR performance. Call 1-877-865-6325, ext. 227, or visit

➔ [www.kodak.com/go/cr](http://www.kodak.com/go/cr)